

PATENT ABSTRACTS OF JAPAN

(11) Publication number : 07-312405
(43) Date of publication of application : 28. 11. 1995

(51) Int. Cl.

H01L 23/50
H01L 21/60
H01L 21/321
H01L 23/28

(21) Application number : 06-102989

(71) Applicant : HITACHI LTD
HITACHI MICRO COMPUT ENG LTD

(22) Date of filing : 17. 05. 1994


(72) Inventor : KANEMOTO KOICHI
NISHIDA TAKAFUMI
SUMIYA AKIRO

(54) SEMICONDUCTOR DEVICE

(57) Abstract:

PURPOSE: To reduce mounting area, and improve mounting efficiency in board mounting, by protruding a part of an inner lead from the bottom surface or the upper surface of a sealing resin part.

CONSTITUTION: An inner lead part 1 is electrically connected with a semiconductor chip 3 via a bump 2 formed on the inner lead part 1. An outer lead part 5 protruding from a resin molded part 4 is surface-mounted on a board or the like. By protruding a part of the inner lead from the bottom surface or the upper surface of the sealing resin part of a semiconductor device, the outer leads are provided in the area occupied by the sealing resin part of the semiconductor device, so that the mounting area is reduced and the mounting efficiency in the board mounting of a semiconductor device is improved.



LEGAL STATUS

[Date of request for examination]

26. 04. 2000

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3243116

[Date of registration]

19. 10. 2001

[Number of appeal against examiner's decision of rejection]